


**Transient Voltage Suppressor
P6SMB Series****1. Features****DO-214AA(SMB)**

- Low profile package
- Ideal for automated placement
- 600 Watt peak pulse power capability with a 10/1000 μ s waveform
- For surface mounted applications to optimize board space
- Excellent clamping capability
- Very fast response time
- Low incremental surge resistance
- RoHS and HF Compliant



DO-214AA(SMB)



Uni-directional



Bi-directional

2. Applications

- Power supply protection
- Automotive application
- Industrial application
- Power management

3. Maximum Ratings and Thermal Considerations (T_A=25°C)

Parameter	Symbol	Value	Units
Peak Pulse Power Dissipation on 10/1000 μ s waveform (Note1,Note2)	P _{PPM}	600	W
Steady State Power Dissipation at T _A =50°C(Note2)	P _D	5.0	W
Operating Junction Temperature	T _J	-55 to +150	°C
Storage Temperature Range	T _{STG}	-55 to +150	°C
Junction to Ambient on printed circuit	R _{θJA}	90	°C/W

Notes :

1. Non-repetitive current pulse, T_A =25°C.
2. Mounted on 5.0mm*5.0mm (0.03mm thick) Copper Pads to each terminal.

 FUZETEC TECHNOLOGY CO., LTD.						NO.	P6SMB Series		
Product Specification and Approval Sheet						Version	P4	Page	2/6

4. Electrical Characteristics (TA=25°C)

Part Number		Device Marking Code		Reverse Stand-off Voltage	Breakdown Voltage Min. @I _r	Breakdown Voltage Max. @I _r	Test Current	Maximum Clamping Voltage @I _{PP}	Peak Pulse Current	Reverse Leakage @ V _{RWM}
Uni-Polar	Bi-Polar	Uni	Bi	V _{RWM} (V)	V _{BR} (V)	V _{BR} (V)	I _r (mA)	V _c (V)	I _{PP} (A)	I _r (uA)
P6SMB6.8A	P6SMB6.8CA	6V8A	6V8C	5.8	6.5	7.1	10	10.5	58.1	1000
P6SMB7.5A	P6SMB7.5CA	7V5A	7V5C	6.4	7.1	7.9	10	11.3	54.0	500
P6SMB8.2A	P6SMB8.2CA	8V2A	8V2C	7.0	7.8	8.6	10	12.1	50.4	200
P6SMB9.1A	P6SMB9.1CA	9V1A	9V1C	7.8	8.7	9.6	1	13.4	45.5	50
P6SMB10A	P6SMB10CA	10A	10C	8.6	9.5	10.5	1	14.5	42.1	10
P6SMB11A	P6SMB11CA	11A	11C	9.4	10.5	11.6	1	15.6	39.1	5
P6SMB12A	P6SMB12CA	12A	12C	10.2	11.4	12.6	1	16.7	36.5	5
P6SMB13A	P6SMB13CA	13A	13C	11.1	12.4	13.7	1	18.2	33.5	1
P6SMB15A	P6SMB15CA	15A	15C	12.8	14.3	15.8	1	21.2	28.8	1
P6SMB16A	P6SMB16CA	16A	16C	13.6	15.2	16.8	1	22.5	27.1	1
P6SMB18A	P6SMB18CA	18A	18C	15.3	17.1	18.9	1	25.5	24.2	1
P6SMB20A	P6SMB20CA	20A	20C	17.1	19.0	21.0	1	27.7	22.0	1
P6SMB22A	P6SMB22CA	22A	22C	18.8	20.9	23.1	1	30.6	19.9	1
P6SMB24A	P6SMB24CA	24A	24C	20.5	22.8	25.2	1	33.2	18.4	1
P6SMB27A	P6SMB27CA	27A	27C	23.1	25.7	28.4	1	37.5	16.3	1
P6SMB30A	P6SMB30CA	30A	30C	25.6	28.5	31.5	1	41.4	14.7	1
P6SMB33A	P6SMB33CA	33A	33C	28.2	31.4	34.7	1	45.7	13.3	1
P6SMB36A	P6SMB36CA	36A	36C	30.8	34.2	37.8	1	49.9	12.2	1
P6SMB39A	P6SMB39CA	39A	39C	33.3	37.1	41.0	1	53.9	11.3	1
P6SMB43A	P6SMB43CA	43A	43C	36.8	40.9	45.2	1	59.3	10.3	1
P6SMB47A	P6SMB47CA	47A	47C	40.2	44.7	49.4	1	64.8	9.4	1
P6SMB51A	P6SMB51CA	51A	51C	43.6	48.5	53.6	1	70.1	8.7	1
P6SMB56A	P6SMB56CA	56A	56C	47.8	53.2	58.8	1	77.0	7.9	1
P6SMB62A	P6SMB62CA	62A	62C	53.0	58.9	65.1	1	85.0	7.2	1
P6SMB68A	P6SMB68CA	68A	68C	58.1	64.6	71.4	1	92.0	6.6	1
P6SMB75A	P6SMB75CA	75A	75C	64.1	71.3	78.8	1	103.0	5.9	1
P6SMB82A	P6SMB82CA	82A	82C	70.1	77.9	86.1	1	113.0	5.4	1
P6SMB91A	P6SMB91CA	91A	91C	77.8	86.5	95.5	1	125.0	4.9	1
P6SMB100A	P6SMB100CA	100A	100C	85.5	95.0	105.0	1	137.0	4.5	1
P6SMB110A	P6SMB110CA	110A	110C	94.0	105.0	116.0	1	152.0	4.0	1
P6SMB120A	P6SMB120CA	120A	120C	102.0	114.0	126.0	1	165.0	3.7	1

NOTE : Specification subject to change without notice.


2025/7/11 Y




Part Number		Device Marking Code		Reverse Stand-off Voltage	Breakdown Voltage Min. @I _T	Breakdown Voltage Max. @I _T	Test Current	Maximum Clamping Voltage @I _{PP}	Peak Pulse Current	Reverse Leakage @ V _{RWM}
Uni-Polar	Bi-Polar	Uni	Bi	V _{RWM} (V)	V _{BR} (V)	V _{BR} (V)	I _T (mA)	V _C (V)	I _{PP} (A)	I _R (uA)
P6SMB130A	P6SMB130CA	130A	130C	111.0	124.0	137.0	1	179.0	3.4	1
P6SMB150A	P6SMB150CA	150A	150C	128.0	143.0	158.0	1	207.0	2.9	1
P6SMB160A	P6SMB160CA	160A	160C	136.0	152.0	168.0	1	219.0	2.8	1
P6SMB170A	P6SMB170CA	170A	170C	145.0	162.0	179.0	1	234.0	2.6	1
P6SMB180A	P6SMB180CA	180A	180C	154.0	171.0	189.0	1	246.0	2.5	1
P6SMB200A	P6SMB200CA	200A	200C	171.0	190.0	210.0	1	274.0	2.2	1
P6SMB220A	P6SMB220CA	220A	220C	185.0	209.0	231.0	1	328.0	1.9	1
P6SMB250A	P6SMB250CA	250A	250C	214.0	237.0	263.0	1	344.0	1.8	1
P6SMB300A	P6SMB300CA	300A	300C	256.0	285.0	315.0	1	414.0	1.5	1
P6SMB350A	P6SMB350CA	350A	350C	300.0	332.0	368.0	1	482.0	1.3	1
P6SMB400A	P6SMB400CA	400A	400C	342.0	380.0	420.0	1	548.0	1.1	1
P6SMB440A	P6SMB440CA	440A	440C	376.0	418.0	462.0	1	602.0	1.0	1
P6SMB480A	P6SMB480CA	480A	480C	408.0	456.0	504.0	1	658.0	0.9	1
P6SMB510A	P6SMB510CA	510A	510C	434.0	485.0	535.0	1	698.0	0.9	1
P6SMB530A	P6SMB530CA	530A	530C	451.0	503.5	557.0	1	725.0	0.8	1
P6SMB540A	P6SMB540CA	540A	540C	459.0	513.0	567.0	1	740.0	0.8	1
P6SMB550A	P6SMB550CA	550A	550C	467.0	522.5	578.0	1	760.0	0.8	1
P6SMB600A	P6SMB600CA	600A	600C	510.0	570.0	630.0	1	828.0	0.8	1




5. Ratings and Characteristic Curves




TVS Transients Clamping Waveform




Peak Pulse Power Rating Curve




Pulse Derating Curve



Pulse Waveform



Typical Junction Capacitance




Steady State Power Dissipation Derating Curve




6. Soldering Parameters

Reflow Condition		Lead-free assembly
Pre Heat	Temperature Max (Ts(min))	150°C
	Temperature Max (Ts(max))	200°C
	Time (min to max) (ts)	60 – 180 secs
Average ramp up rate (Liquidus Temp (TL) to peak)		3°C/second max
Ts(max) to TL - Ramp-up Rate		3°C/second max
Reflow	Temperature (TL) (Liquidus)	217°C
	Time (min to max) (tL)	60 – 150 seconds
Peak Temperature (TP)		260°C
Time within 5°C of actual peak Temperature (tp)		20 – 40 seconds
Ramp-down Rate		6°C/second max
Time 25°C to peak Temperature (TP)		8 minutes max.
Do not exceed		260°C




7. Recommended Pad Lay Out Dimensions




Ref.	Millimeters		Inches	
	Min.	Max.	Min.	Max.
A	2.20	-	0.087	-
B	1.45	-	0.057	-
C	-	2.55	-	0.010
D	1.45	-	0.057	-
E	5.60 REF		0.220 REF	

8. Part Numbering and Marking System

Part Numbering System




Marking System



NOTE : Specification subject to change without notice.



9. DO-214AA(SMB) Package Information



Ref.	Millimeters		Inches	
	Min.	Max.	Min.	Max.
A	1.80	2.20	0.071	0.087
B	4.30	4.70	0.170	0.185
C	3.40	3.90	0.134	0.153
D	2.15	2.55	0.085	0.100
E	1.00	1.50	0.039	0.059
F	0.02	0.20	0.001	0.008
G	5.10	5.50	0.200	0.216
H	0.15	0.30	0.006	0.012

10. Packaging Specification

Part Number	Quantity	Reel Size
P6SMBxx(CA)	3000	13" inch

